

CONTACT: SUNNY
 TEL: 0086-13483036671
 EMAIL: sunnyzhou0707@hotmail.com
 SKYPE: juhongcasting



Model	Output		Voltage (V)	Current (A)	Speed (r.p.m)	Eff (%)	Power Factor	Start Torque Rating	Start Current Rating	Max Torque Rating	Min Torque Rating	Noise dBA	Weight kGS
	kW	HP											
2-Pole Synchronous 3000RPM 50Hz													
YY2 80A2	0.75	1.0	380	1.80	2890	75.0	0.83	2.2	6.1	2.3	1.5	67	16
YY2 80B2	1.1	1.5	380	2.60	2900	76.2	0.84	2.2	6.9	2.3	1.5	67	17
YY2 90S2	1.5	2.0	380	3.40	2900	78.5	0.84	2.2	7.0	2.3	1.5	72	22
YY2 90L2	2.2	3.0	380	4.80	2930	81.0	0.85	2.2	7.0	2.3	1.4	72	25
YY2 100L2	3.0	4.0	380	6.30	2930	82.6	0.87	2.2	7.5	2.3	1.4	76	33
YY2 112M2	4.0	5.5	380	8.10	2930	84.2	0.88	2.2	7.5	2.3	1.4	77	45
YY2 132SA2	5.5	7.5	380	11.0	2940	85.7	0.88	2.2	7.5	2.3	1.2	80	64
YY2 132SB2	7.5	10.0	380	15.0	2950	87.0	0.88	2.2	7.5	2.3	1.2	80	70
YY2 160MA2	11	15	380	21.3	2950	88.4	0.89	2.2	7.5	2.3	1.2	86	117
YY2 160MB2	15	20	380	28.7	2970	89.4	0.89	2.2	7.5	2.3	1.2	86	125
YY2 160L2	18.5	25	380	34.6	2970	90.0	0.90	2.2	7.5	2.3	1.1	86	147
YY2 180M2	22	30	380	40.9	2970	90.5	0.90	2.0	7.5	2.3	1.1	89	180
YY2 200LA2	30	40	380	55.4	2970	91.4	0.90	2.0	7.5	2.3	1.1	92	240
YY2 200LB2	37	50	380	67.7	2980	92.0	0.90	2.0	7.5	2.3	1.1	92	255
YY2 225M2	45	60	380	82.3	2980	92.5	0.90	2.0	7.5	2.3	1.0	92	309
YY2 225M2	55	75	380	101.0	2980	93.0	0.90	2.0	7.5	2.3	1.0	93	403
YY2 280S2	75	100	380	134.0	2980	93.6	0.90	2.0	7.0	2.3	0.9	94	544
YY2 280M2	90	125	380	160.0	2980	93.9	0.91	2.0	7.1	2.3	0.9	94	620
YY2 315S2	110	150	380	195.0	2980	94.0	0.91	1.8	7.1	2.2	0.9	96	960
YY2 315M2	132	180	380	233.0	2980	94.5	0.91	1.8	7.1	2.2	0.9	96	1080
YY2 315LA2	160	220	380	279.0	2980	94.6	0.92	1.8	7.1	2.2	0.9	99	1160
YY2 315LB2	200	270	380	348.0	2980	94.8	0.92	1.8	7.1	2.2	0.8	99	1190
Y2 355M2	250	340	380	433.0	2980	95.2	0.92	1.6	7.1	2.2	0.8	103	1760
Y2 355L2	315	430	380	544.0	2980	95.4	0.92	1.6	7.1	2.2	0.8	103	1850
4-Pole Synchronous 1500RPM 50Hz													
YY2 80A4	0.55	0.75	380	1.50	1400	71.0	0.75	2.4	5.2	2.3	1.7	58	17
YY2 80B4	0.75	1.0	380	2.00	1400	73.0	0.76	2.3	6.0	2.3	1.6	58	18
YY2 90S4	1.1	1.5	380	2.90	1400	76.2	0.77	2.3	6.0	2.3	1.6	61	22
YY2 90L4	1.5	2.0	380	3.70	1400	78.5	0.78	2.3	6.0	2.3	1.6	61	27
YY2 100L14	2.2	3.0	380	5.10	1420	81.0	0.81	2.3	7.0	2.3	1.5	64	34
YY2 100L24	3.0	4.0	380	6.80	1420	82.6	0.82	2.3	7.0	2.3	1.5	64	38
YY2 112M4	4.0	5.5	380	8.80	1440	84.2	0.82	2.3	7.0	2.3	1.5	65	43
YY2 132S4	5.5	7.5	380	11.8	1440	85.7	0.83	2.3	7.0	2.3	1.4	71	68
YY2 132M4	7.5	10	380	15.5	1440	87.0	0.84	2.3	7.0	2.3	1.4	71	81
YY2 160M4	11	15	380	22.3	1460	88.4	0.84	2.2	7.0	2.3	1.4	75	123
YY2 160L4	15	20	380	30.0	1460	89.4	0.85	2.2	7.5	2.3	1.4	75	144
YY2 180M4	19	25	380	36.4	1470	90.0	0.86	2.2	7.5	2.3	1.2	76	182
YY2 180L4	22	30	380	43.1	1470	90.5	0.86	2.2	7.5	2.3	1.2	76	190
YY2 200L4	30	40	380	57.4	1470	91.4	0.86	2.2	7.2	2.3	1.2	79	270
YY2 225S4	37	50	380	69.9	1480	92.0	0.87	2.2	7.2	2.3	1.2	81	284
YY2 225M4	45	60	380	84.7	1480	92.5	0.87	2.2	7.2	2.3	1.1	81	320
YY2 250M4	55	75	380	103	1480	93.0	0.87	2.2	7.2	2.3	1.1	83	427
YY2 280S4	75	100	380	140	1480	93.6	0.88	2.2	6.8	2.3	1.0	86	562
YY2 280M4	90	125	380	167	1490	93.9	0.88	2.2	6.8	2.3	1.0	86	667
YY2 315S4	110	150	380	201	1490	94.5	0.88	2.1	6.9	2.2	1.0	93	1000
YY2 315M4	132	180	380	240	1490	94.8	0.88	2.1	6.9	2.2	1.0	93	1100
YY2 315LA4	160	220	380	287	1490	94.9	0.89	2.1	6.9	2.2	1.0	97	1160
YY2 315LB4	200	270	380	359	1490	94.9	0.89	2.1	6.9	2.2	0.9	97	1270
Y2 355M4	250	340	380	443	1485	95.2	0.90	2.1	6.9	2.2	0.9	101	1700
Y2 355L4	315	430	380	556	1485	95.2	0.90	2.1	6.9	2.2	0.8	101	1850
6-Pole Synchronous 1000RPM 50Hz													
Y2 80A6	0.37	0.50	380	1.30	900	62.0	0.70	1.9	4.7	2.0	1.5	54	17
Y2 80B6	0.55	0.75	380	1.80	900	65.0	0.72	1.9	4.7	2.1	1.5	54	19
YY2 90S6	0.75	1.0	380	2.30	910	69.0	0.72	2.0	5.3	2.1	1.5	57	23
YY2 90L6	1.1	1.5	380	3.20	910	72.0	0.73	2.0	5.5	2.1	1.3	57	25
YY2 100L6	1.5	2.0	380	3.90	940	76.0	0.75	2.0	5.5	2.1	1.3	61	33
YY2 112M6	2.2	3.0	380	5.60	940	79.0	0.76	2.0	6.5	2.1	1.3	65	45
YY2 132S6	3.0	4.0	380	7.40	960	81.0	0.76	2.1	6.5	2.1	1.3	69	63
YY2 132MA6	4.0	5.5	380	9.70	960	82.0	0.76	2.1	6.5	2.1	1.3	69	73
YY2 132MB6	5.5	7.5	380	12.9	960	84.0	0.77	2.1	6.5	2.1	1.3	69	84
YY2 160M6	7.5	10	380	16.5	970	86.0	0.77	2.0	6.5	2.1	1.3	73	109
YY2 160L6	11	15	380	24.1	970	87.5	0.78	2.0	6.5	2.1	1.2	73	147
YY2 180L6	15	20	380	31.5	970	89.0	0.81	2.0	7.0	2.1	1.2	73	195
YY2 200LA6	18.5	25	380	38.5	970	90.0	0.81	2.1	7.0	2.1	1.2	76	220
YY2 200LB6	22	30	380	44.6	970	90.0	0.83	2.0	7.0	2.1	1.2	76	250
YY2 225M6	30	40	380	59.3	990	91.5	0.84	2.0	7.0	2.1	1.2	76	292
YY2 250M6	37	50	380	71.0	980	92.0	0.86	2.1	7.0	2.1	1.2	78	408
YY2 280S6	45	60	380	86.0	980	92.5	0.86	2.1	7.0	2.0	1.1	80	536
YY2 280M6	55	75	380	105	980	92.8	0.86	2.1	7.0	2.0	1.1	80	595
YY2 315S6	75	100	380	141	990	93.5	0.86	2.0	6.7	2.0	1.0	85	990
YY2 315M6	90	125	380	169	990	93.8	0.86	2.0	6.7	2.0	1.0	85	1080
YY2 315LA6	110	150	380	205	990	94.0	0.86	2.0	6.7	2.0	1.0	85	1150
YY2 315LB6	132	180	380	244	990	94.2	0.87	2.0	6.7	2.0	1.0	85	1210
Y2 355MA6	160	220	380	292	990	94.5	0.88	1.9	6.7	2.0	1.0	92	1600
Y2 355MB6	200	270	380	365	990	94.5	0.88	1.9	6.7	2.0	0.9	92	1700
Y2 355L6	250	340	380	455	990	94.5	0.88	1.9	6.7	2.0	0.9	92	1800
8-Pole Synchronous 750RPM 50Hz													
Y2 80A8	0.18	0.25	380	0.88	680	51.0	0.61	1.8	3.3	1.9	1.3	52	17
Y2 80B8	0.25	0.33	380	1.15	680	54.0	0.61	1.8	3.3	1.9	1.3	52	19
Y2 90S8	0.37	0.50	380	1.50	680	62.0	0.61	1.8	4.0	1.9	1.3	56	23
Y2 90L8	0.55	0.75	380	2.20	700	63.0	0.61	1.8	4.0	2.0	1.3	56	25
Y2 100LAB	0.75	1.0	380	2.40	700	70.0	0.67	1.8	4.0	2.0	1.3	59	33
Y2 100LB8	1.1	1.5	380	3.30	700	72.0	0.69	1.8	5.0	2.0	1.2	59	38
Y2 112M8	1.5	2.2	380	4.50	700	74.0	0.70	1.8	5.0	2.0	1.2	61	50
YY2 132S8	2.2	3.0	380	6.00	710	79.0	0.71	1.8	6.0	2.0	1.2	64	63
YY2 132M8	3.0	4.0	380	7.90	710	80.0	0.73	1.8	6.0	2.0	1.2	64	79
YY2 160MA8	4.0	5.5	380	10.2	720	81.0	0.73	1.9	6.0	2.0	1.2	68	118
YY2 160MB8	5.5	7.5	380	13.6	720	83.0	0.74	1.9	6.0	2.0	1.2	68	119
YY2 160L8	7.5	10	380	17.7	720	85.5	0.75	1.9	6.0	2.0	1.2	68	145
YY2 180L8	11	15	380	25.1	730	87.5	0.75	2.0	6.5	2.0	1.1	70	184
YY2 200L8	15	20	380	34.0	730	88.0	0.76	2.0	6.6	2.0	1.1	73	250
YY2 225S8	18.5	25	380	40.6	730	90.0	0.76	1.9	6.6	2.0	1.1	73	266
YY2 225M8	22	30	380	47.4	730	90.5	0.78	1.9	6.6	2.0	1.1	73	292
YY2 250M8	30	40	380	64.0	740	91.0	0.79	1.9	6.6	2.0	1.1	75	405
YY2 280S8	37	50	380	78.0	740	91.5	0.79	1.9	6.6	2.0	1.1	76	520
YY2 280M8	45	60	380	94	740	92.0	0.79	1.9	6.6	2.0	1.0	76	592
YY2 315S8	55	75	380	111	740	92.8	0.81	1.8	6.6	2.0	1.0	82	1000
YY2 315M8	75	100	380	151	740	93.5	0.81	1.8	6.2	2.0	0.9	82	1100
YY2 315LA8	90	125	380	178	740	93.8	0.82	1.8	6.4	2.0	0.9		